

## ASTOL SCRUBBER DRYERS



AS-510C



AS-510B



AS-820R

TECHNICAL SPECIFICATIONS	AS 820R	AS 510B	AS 510C
Cable length (m)	-	-	25ft/black
Vacuum Andor Type	Universal 2-stage	Universal 2-stage	Universal 2-stage
Vacuum Motor Power (hp)	560	500	1000
Brush Motor Power (hp)	900	900	900
Voltage (V)	30V, 312AH	24V, 111Ah	220-240
Frequency (Hz)			50-60
IP Protection Class	IP 3A	IP 3A	IP 3A
Productivity Rate (L/2H)	5000	2200	1800
Rated Power (hp)	2420	1000	1900
Airflow (m³/h)	58	48	50
Vacuum (PSIA/PSIA)	100/16	14/0/1.8	18/0/1.8
Sound Power Level (dB(A) @ 70m)	89	70	70
Brush Cleaning (m/min)	820	510	510
Brush Rotation Speed (RPM)	170	282	282
Squeeze width mm	1100	755	755
Tank Capacity Solution/Recovery (L)	125/132	50/55	50/55
Length x width x height (mm)	1680x1020x1310	1300x1000x850	1100x1000x850
Brush Pressure (kg)	70	38 - 50	38 - 50
Weight without batteries (kg)		133	133

## ASTOL - MANUAL SWEEPER

TECHNICAL FEATURES	
Cleaning capacity	1500 m <sup>2</sup> /hr
Cleaning width (main brush)	500 mm
Cleaning width of side brush	200 mm
Total cleaning width	700 mm
Machine width (with side brush)	750 mm
Height to the top of the Handle	950 mm
Hopper Capacity	35 lts
Main Wheel Diameter	250 mm
Weight	35 kgs
Dimension (LxBxH)	760x 750x 950 mm
Weight (kg)	20kg
Note	



## ASTOL - WALK BEHIND BATTERY SWEEPER



TECHNICAL FEATURES		BATTERY LIFE
Power Source		Ametech
Motor Brand		Ametech
Max Power		4.0KW
Max Speed (km/h)		6.2
Fuel		oil
Cylinders		oil
Cooling System		AIR
Productivity Rate 1 Side Brush Theoretical/Actual (m <sup>2</sup> /H)		5500
Working width (m)		1.50
Working width W/2 Side Brushes (m)		1.10
Min. Turn-Around Axle Width (m)		-
Hopper Volume (L)		40
Max. Dumping Height (m)		-
Main Filter Area (m <sup>2</sup> )		1.5
Length x width x height (mm)		90
Shipping Weight (kg)		



ASTOL CLEANTECH (P) LIMITED  
 Contact: D-77 Sector -7, Noida Pin-201301  
 Mob: 9810967072, 9310356148 Land: 0120-4313834  
 Corporate Mail Id: astolcleantech@yahoo.in  
 Website: www.astol.in

CHANNEL PARTNER

clean almost anything



www.astol.in



**COMMERCIAL & INDUSTRIAL VACUUM CLEANER**



ITEM	MODEL	TANK DETAILS	VACUUM MOTOR DETAILS				SOUND LEVEL			ABSORBED POWER		LOGISTIC DATA	
			MOTOR		AIR FLOW		SECTON	dB	VOLT	KW	HZ	L*W*H (MM)	KG
10220065I	SF 65-1	60	Induction turbine	3000	87	310	70	400	3	50			103
102200803	SF 80-3M	80	Dual turbine	1000	180	270	84	230	3	50			
102200802	SF 60-2M	60	Dual turbine	1000	120	270	80	230	2	50			
102200910	SF 10	25	Dual turbine	1000	53	250	72	230	1	50			
102200151	SF 15	11	Dual turbine	1000	60	250	72	230	1	50			

**ASTOL MULTY FUNCTION SINGLE DISC POLISHER**

TECHNICAL SPECIFICATIONS	MS 1200	MS 1500
Cable length (M)	150black	150black
Voltage (V)	220-240	220-240
Frequency (Hz)	50-60	50-60
IP Protection Class	IP65	IP65
Rated Power (KW)	1.2	1.5
Sound Power Level (DWA) (dB (A) (1m))	68	68
Cleaning Pushwidth (mm)	430	430
Tank Capacity (L)	11	11
Brush Rot Speed (RPM)	175	175
Weight (KG)	44	46



**HPH HOT PRESSURE WASHER**



MODEL	OPERATED PUMP PRESSURE	FLOW RATE	TECHNICAL PUMPS DATA			ABSORBED POWER			DIMENSIONS DATA		
MODEL	BAR	MPA	LTR/HOUR	BPM	TYPE	PISTON TYPE	VOLT	KW	HZ	L*W*H (MM)	KG
HPH 6958R-6670	200	20	900	1450	Plunger	3 Ceramic	400	7.4	3-50	980x510x960	98
HPH 6958R-6640	230	23	600	1450	Plunger	3 Ceramic	230	3	3-50	1000x510x920	82
HPH 7858R-7850	150	15	900	1450	Plunger	3 Ceramic	400	5	3-50	980x510x920	94

**HPC COLD PRESSURE WASHER**



**ASTOL - STATIONARY PRESSURE WASHER COLD SERIES**



MODEL	OPERATED PUMP PRESSURE		FLOW RATE		CLEANING EFFICIENCY		TECHNICAL PUMPS DATA			IP PROTECTION		ABSORBED POWER		DIMENSIONS DATA	
	BAR	MPA	M3L	LTR/HOUR	KG/FORCE	BPM	TYPE	PISTON TYPE	IP	VOLT	KW	HZ	L*W*H (MM)	KG	
HPC3-955	200	20	900	5.2	1450	2800	Plunger	3 Ceramic	K5-S1	400	9	3-50	620x500x950	63	
HPC3-780	130	13	720	3.3	1450	2800	Plunger	3 Ceramic	K5-S1	230	3.1	1-50	390x300x900	44	
HPC3-747	100	10	540	2.7	2800	2800	Wobble plate	355	IP65-S1	230	3.1	1-50	390x300x900	32	
HPC3-630	120	12	600	2.6	1450	2800	Plunger	3 Ceramic	K5-S1	230	2.6	1-50	390x240x230	21	
HPC2-590	160	15	500	2.4	2800	2800	Plunger	3 Ceramic	K5-S1	230	3	1-50	390x240x230	21	
HPC2-610	160	15	600	2.8	2800	2800	Wobble plate	355	K5-S1	230	2.8	1-50	390x240x230	21.5	
HPC-610	130	12	500	2.4	2800	2800	Plunger	3 Ceramic	K5-S1	230	2.2	1-50	370x240x240	18	
HPC-116	100	10	360	1.5	3400	2800	Plunger	3 Ceramic	K5-S1	230	1.3	1-50	230x220x440	6.5	